RoofLITE+

TECHNICAL DATA SHEET

SOLID PVC



APPLICABLE
In public and domestic buildings
In heated, inhabited rooms
In roof pitch range of 15°-90°
Suitable on all common roofings with proper flashing
FEATURES
Centre pivot u-PVC roof window
Toughened outer glass
Excellent insulation
High humidity resistance
Maintenance free PVC profile
Elegant bottom handle
Two passive ventilation positions via handle
Double gasket system between frame and sash
Double Low-e coating
Easy installation
10 year guarantee
MATERIAL
Lead free PVC
Steel reinforcement
Polystyrene insulation insertion
COVER PARTS
Aluminium, lacquered, grey colour (RAL 7043)
HANDLE
Ergonomically designed moulded zinc handle, lacquered
HINGE
Pivot hinge

CE

10 YEAR GUARANTEE

APY B900


PANE	
Construction	4-16-4H
Thickness of glazing (mm)	24 mm
Low E	■■
Gas	Argon
Toughened	■
U_g *(W/m²K)*	1.0
Total solar energy transmittance	0.55
WINDOW	
U_w *(W/m²K)*	1.3
Water tightness	E1500
Air permeability	Class 4
Resistance to wind load	Class C4
Sound reduction	32 (-1,-5) dB
COLOUR	
White	■

MEASURES

CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m²
C2A	55 x 78 cm	55 cm	77,8 cm	39,8 cm	64,9 cm	37,3 cm	59 cm	0.220
C4A	55 x 98 cm	55 cm	97,8 cm	39,8 cm	84,9 cm	37,3 cm	79 cm	0.295
F4A*	66 × 98 cm	66 cm	117,8 cm	50,8 cm	104,9 cm	48,,3 cm	99 cm	0.478
F6A	66 x 118 cm	66 cm	117,8 cm	50,8 cm	104,9 cm	48,3 cm	99 cm	0.478
M4A	78 x 98 cm	78 cm	97,8 cm	62,8 cm	84,9 cm	60,3 cm	79 cm	0.476
M6A	78 x 118 cm	78 cm	117,8 cm	62,8 cm	104,9 cm	60,3 cm	99 cm	0.597
M8A	78 x 140 cm	78 cm	139,8 cm	62,8 cm	126,9 cm	60,3 cm	121 cm	0.729
M10A*	78 ×160 cm	78 cm	159,8 cm	62,8 cm	146,9 cm	60,3 cm	141 cm	0.850
S6A	114 x 118 cm	114 cm	117,8 cm	98,8 cm	104,9 cm	96,3 cm	99 cm	0.953

* Only TFX and UFX flashings are available


FLASHING RANGE FOR DIFFERENT ROOFING MATERIALS**




SLATE
Suitable for slates and flat roofing, up to 8mm (max overall thickness is 16 mm)




TILE
Suitable for low profile tiles and profiled materials between 16-50 mm



INTERLOCKING FLAT TILE
Suitable for interlocking flat tiles between 16 and 50 mm.



UNIVERSAL
Suitable for high profiled tiles and profiled materials between 16-120 mm



STANDING SEAM
Suitable for standing seam steel sheet coverings

* Combi solutions are also available, please contact your dealer for details.


BLIND RANGE*



BLACKOUT



AWNING



ROLLER SHUTTER

contrio.com

*For the right product code of blinds, please take the type of blind, size of RW and colour code, e.g. DUA C2A 4219